



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GCC-50% G12+ LONG TIME

100% organic coolant

DESCRIPTION

100% organic, anti-freeze, all-weather coolant, specially formulated to be used in any type of cooling circuit, both sealed (C.C.) and open. The main purpose is to cool the engine and lower the freezing point of the water. Suitable for EURO VI vehicles.

PERFORMANCE

STANDARDS:

ASTM D-3306 / D-4985
UNE 26-361-88
SAE J 1034
NATO S-759
BS 6580

SPECIFICATIONS:

MB 325.3
GM QL 130100 / 1899M
MAN 324
Renault 41-01-001
Ford WSS-M97B44-C / WSS-M97B49-A
Chrysler MS-9176 / MS-12106
Mack 014GS17004
Cummins 90T8-4
VW TL 774-D (G12) / TL 774-F (G12+)
Deutz MWN 0199-2091

It provides high operational stability, which means a long service life and therefore significant savings. Particularly suitable for cooling circuits and radiators made of aluminium or its alloys.

Product free of NAPS (Nitrites, Phosphates, Amines, Silicates).

CONDITIONS OF USE

Maintenance interval according to each manufacturer's recommendations and adapted to your own use. No prior dilution required, ready-to-use product.

Rev. 02/24



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.





PERFORMANCE LUBRICATION

PRODUCT INFORMATION

TECHNICAL FEATURES

COLOUR: PINK / GREEN / YELLOW / BLUE
DENSITY: 1.065 gr/cm³
pH: 8

FREEZING POINT: -38 °C / -36.4 °F
FLASHPOINT (open): 108 °C / 226.4 °F
FLASHPOINT (closed): 145 °C / 293 °F

Rev. 02/24



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME
Subsidized per 176/2012

