



Mobil™ 75W-80 MULTI-VEHICLE

Manual Gear Oil

Product Description

Mobil 75W-80 Multi Vehicle provides excellent bearing and gear protection as well as proven synchroniser performance in a wide range of applications. Its versatility of use is a plus for workshops aiming to ensure an optimal service to their customers while simplifying their operations and product management.

Recommended by Comma for applications requiring any of the following:

BMW MTF LT-2, Ford M2C 186-A, GM 1940768, MTF 94, Nissan MT-XZ TL (JR Type), Nissan MT-XZ, Tranself TRX, NFP, TRP, TRZ, Volvo 97308, API GL-4, Honda MTF, Honda MTF - II, Honda MTF - III, Ford M2C186-A, ABMW MTF LT-2, Special gear oil

Product Features:

- High Fleet coverage to reduce inventory.
- Advanced friction profile and proven synchroniser performance for smooth shifting.
- Robust corrosion protection to ensure lifetime of parts.
- Maintains performance at low temperatures. Critical to ensure protection at start up.
- Recommended for a variety of BMW, Vauxhall/Opel, Mini, Land Rover, Honda, Volvo and MG applications and generally where a 75W-80, API GL-4 oil is specified.

Handling:

- Health and safety recommendations for this product can be found on the Material Safety Data Sheet

Typical Inspections Data:	
Density @ 20°C	0.853 g/cm3
Viscosity @ 100 °C	8.7 cSt
Viscosity @ 40 °C	50 cSt
Calcium	0.29%
Phosphorus	0.05%
Colour	Brown
Pour Point	-39 °C